

AntiFreeze

Anti-Freeze Admixture

Product Description:

A naphthalene formaldehyde sulphonate-based admixture that does not contain chlorine. It increases the cold air processability of the cementitious mixture added in, provides high resistance, and plasticizing quality by reducing the water content.

Areas of applications:

- In all cementitious productions

Features:

- Increases the resistance values of the mortar
- Shortens the duration of demoulding
- Increases the freezing and dissolving resistance
- Forms a waterproof and compact mixture
- Increases the resistance of abrasion

Technical data:

Colour	Brown
Unit Volume Weight (kg / lt)	1,10 ± 0,2
Clorine Content	< 1%
Alkali Content	< %10

Technical data are approximately provided according to a temperature of + 20°C and a relative humidity of 50%.

Coverage:

Approx. 2% of the cement content in the mixture should be consumed.
The coverage amounts are theoretical.

Packaging:

In 30 kg plastic drums

Storage:

- They should be protected from frost and adverse air conditions.
- They should be kept in a dry and cool place.
- The opened drums should be closed immediately and the ones left open should be disposed.
- Shelf life is maximum 12 months conditional to complying with the abovementioned storage conditions.

Risk Signs :

R23/24/25 : Poisonous when inhaled, swallowed and contacted with skin.

Security signs:

S2: Keep out of reach of children.

S3: Keep cool.

S9: Keep the package dry.

S26: Rinse with water thoroughly when contacted with eyes and consult a doctor.

S28: Rinse with water thoroughly when contacted with skin and consult a doctor.

S29: Do not throw in the drain.

S36/37/39: Wear suitable protective clothing, protective gloves and glasses / mask during the operation.

BOSTIK is only responsible for the product quality and cannot be held responsible for its mis-use except for the recommendations regarding where and/or how the product shall be used. This technical bulletin hereby is valid until it is renewed. BOSTIK's right to amend the products in accordance with technical developments is reserved.



Akçaburgaz Mh. ALKOP Sit. 1575 Sk. C2 Blok No.5-14 Esenyurt 34555 İstanbul
Tel. (+90 212) 858 01 26 Fax. (+90 212) 858 01 34
info@bostik.com.tr - www.bostik.com.tr