

Çekomastik 018

Butyl Sealant

Product Description:

Çekomastik 018 is a one component, polyisobutylene-based sealing material.

Areas of applications:

- Used as a sealing material in air conditioning channels.

Features:

- Maintains its characteristics for a long time
- Contains metal sheet protective and corrosion preventive chemical materials
- Prevents the gaps from humidity and dust after filled
- Resistant to aging, weather conditions and UV lights

Technical data:

Colour	Black, grey
Density (gr/cm ³)	1,2 ± 0,2
Viscosity (cp)	200.000 – 400.000
Flow rate (gr/min)	200 - 800

Technical data are approximately provided according to a temperature of + 20°C and a relative humidity of 50%.

Preparing the substrate:

The application surfaces should be durable, clean, dry and grease- and dust-free.

Application:

- It is easily applied on the surface mechanically or with a spatula.
- The opened products should be consumed soon.
- The application should be carried out at the temperatures between -5°C and +40°C.
- The application workshop should be ventilated since it contains solvents.

Cleaning after the application:

The contaminated areas and used tools should be cleaned with white spirit or alcohol.

Packaging:

In 20 kg metal drums

Storage:

- They should be protected from water, frost and adverse air conditions.
- They should be kept dry and cool on wooden palettes.
- The opened products should be consumed immediately.
- Maximum 2 metal drums are stacked on each other.
- Shelf life is maximum 2 year conditional to complying with the abovementioned storage conditions.

BOSTIK is only responsible for the product quality and cannot be held responsible for its mis-use except for the recommendations regarding where and/or how the product shall be used. This technical bulletin hereby is valid until it is renewed. BOSTIK's right to amend the products in accordance with technical developments is reserved.



Akçaburgaz Mh. ALKOP Sit. 1575 Sk. C2 Blok No.5-14 Esenyurt 34555 İstanbul
Tel. (+90 212) 858 01 26 Fax. (+90 212) 858 01 34
info@bostik.com.tr - www.bostik.com.tr