

ClimaTech Hammared Plug for Aerated Plug

Plastic Nailed Hammered Plug

Product description :

EPS - F40 and EPS - F32 heat insulating plates that are used in ClimaTech Energy Saving systems are plastic nailed plug special for mechanical installation in only aerated concrete surfaces.

Technical data :

Minimum anchorage size	≥ 65
Application areas	Aerated concrete
Diameter of the hole (mm)	10
Diameter of the plate (mm)	60
Sleeve	Polyamid

Consumption :

6 unit/m²

Packaging :

160 mm, 200 pcs in 1 box

ClimaTech Hammared Plug for Aerated Plug

Steel Nailed Hammered Plug

Product description :

EPS - F40 and EPS - F32 heat insulating plates that are used in ClimaTech Energy Saving systems are steel nailed plug special for mechanical installation in only aerated concrete surfaces.

Technical data :

Minimum anchorage size	≥ 65
Application areas	Aerated concrete
Diameter of the hole (mm)	10
Diameter of the plate (mm)	60
Sleeve	Polyamid

Consumption :

6 unit/m²

Packaging :

160 mm, 200 pcs in 1 box

BOSTIK is only responsible for the product quality and cannot be held responsible for its mis-use except for the recommendations regarding where and/or how the product shall be used. This technical bulletin hereby is valid until it is renewed. BOSTIK's right to amend the products in accordance with technical developments is reserved.



Akçaburgaz Mh. ALKOP Sit. 1575 Sk. C2 Blok No.5-14 Esenyurt 34555 İstanbul
Tel. (+90 212) 858 01 26 Fax. (+90 212) 858 01 34
info@bostik.com.tr - www.bostik.com.tr