

Framol

Form Oil

Product Description:

Framol is ready-to-use, mineral oil-based form oil that ensures all kind of used moulds to dismantle easily after pouring concrete and provides a smooth surfaced concrete.

Areas of applications:

- In pouring works
- In wooden, steel, plywood and composite moulds

Features:

- Provides easy dismantling of the mould
- Extends the life of the used mould
- Suitable for heating and steam curing applications. It is not affected from curing temperatures
- Minimizes the air bubbles which may occur in the concrete

Technical data:

Colour	Oily yellow / bright
Unit Volume Weight (kg / lt)	0,85 ± 0,2
pH	6 - 7
Flash point	+90°C

Technical data are approximately provided according to a temperature of + 20°C and a relative humidity of 50%.

Coverage:

It varies depending on the newness and absorbency of the mould.

In wooden, plywood and steel moulds, when 1 lt of Bostik Framol form oil is applied with a roller, approximately 25 m² mould surface is oiled; when it is sprayed with a machine having 2 – 4 bar of pressure, about 40 m² mould surface is oiled.

The coverage amounts are theoretical and it is recommended to do coverage-controlled sample application before treatment.

Packaging:

In 30 kg plastic drums

Storage:

- They should be protected from frost and adverse air conditions.
- They should be kept in a dry and cool place.
- The opened drums should be closed immediately and the ones left open should be disposed.
- Shelf life is maximum 12 months.

Risk Signs :

R23/24/25 : Poisonous when inhaled, swallowed and contacted with skin.

Security signs:

S2: Keep out of reach of children.

S3: Keep cool.

S9: Keep the package dry.

S26: Rinse with water thoroughly when contacted with eyes and consult a doctor.

S28: Rinse with water thoroughly when contacted with skin and consult a doctor.

S29: Do not throw in the drain.

S36/37/39: Wear suitable protective clothing, protective gloves and glasses / mask during the operation.

BOSTIK is only responsible for the product quality and cannot be held responsible for its mis-use except for the recommendations regarding where and/or how the product shall be used. This technical bulletin hereby is valid until it is renewed. BOSTIK's right to amend the products in accordance with technical developments is reserved.



Akçaburgaz Mh. ALKOP Sit. 1575 Sk. C2 Blok No.5-14 Esenyurt 34555 İstanbul
Tel. (+90 212) 858 01 26 Fax. (+90 212) 858 01 34
info@bostik.com.tr - www.bostik.com.tr