

# Meister ASS

## Gypsum Satin Plaster

### Product Description:

A gypsum satin smoothing plaster that is prepared by reinforcement with environmentally friendly chemicals and plaster. It is manually applied and used for smoothing the surface before painting, and produced in accordance with European Union Standards.

### Areas of applications:

- Interiors
- On walls and ceilings
- On all kinds of stone and stone derivative bricks, pumice concrete, briquette, aerated concrete, concrete plates and exposed concrete

### Features:

- Manually applied
- Makes the surfaces ready for coating with materials, such as paint or wall paper
- Can be applied on all gypsum plate and plastered surfaces
- High compressive strength
- Freezes without cracks
- Plastic consistency, easy to apply
- Hydraulic bonding quality
- Fireproof

### Technical data:

Dmax (mm)	1
Colour	White
Applicable Thickness (mm)	5
Dry Unit Volume Weight (kg / lt)	1,0 ± 0,2
Waiting Time in Container (minute)	30
Run Duration (min)	~ 90
Drying Time (hour)	~ 24
Mixture water amount (for 40 kg dry mortar)	20 - 23lt
Environment temperature for application	Between +5°C and +35°C

Technical data are approximately provided according to a temperature of + 20°C and a relative humidity of 50%.

### Preparing the substrate :

- The substances such as dust, dirt, oil, etc.; residues and wastes like cement, plaster and concrete should be removed from the surface. Cracked and weak surfaces should be cleaned from the application surface. The floors and cracks which require repair should be filled or repaired with cement-based surface mortars or the material itself minimum 3-4 days before the application.
- Concrete, plastered walls and ceilings should be wet enough and primed with Meister BBA minimum 24 hours before when necessary.
- Very smooth and slippery surfaces should be roughened up by combing, dampened sufficiently, pre-sprayed or primed with Meister BBA. This is significant in terms of adhering gypsum plaster on the surface thoroughly and not being cracked.
- In case of using surface additives, plaster bearers or plaster-framed concrete, the manufacturer's advice should be followed.
- In required areas (glass edges, concrete and brick connection spots, moveable areas, etc.), plaster mesh should be used.

### Application:

- Meister ASS in dusty state is slowly sprayed into a clean container filled with some clean water at normal environment temperature and rested for 2-3 minutes.
- The mixture is mixed with a low circle mixer until a smooth and homogenous mixture is obtained. Mixing time should be minimum 3 minutes.
- In fairly inclined walls, depth gauging is recommended in order to obtain a smooth surface.

- It is recommended to use plaster mesh in connection places of different types of construction chemicals (e.g. concrete columns and bricks) and aluminium in corners (e.g. beams and columns).
- The surface that is rested for a sufficient time to dry becomes suitable for the paint.

**After application:**

- In initial days, newly applied surfaces should be protected from rain, frost, severe air stream, direct sunlight and water.
- All kind of application like paint or wall paper on the plastered surface should be done after the paint is dried completely.
- While making any coating application on the treated plaster, the manufacture's advice should be followed.

**Coverage:**

1 kg/m<sup>2</sup> for approx. 1 mm thickness.

The coverage amounts are theoretical and it is recommended to do coverage-controlled sample application before treatment.

**Packaging:**

In 30 kg pp bags, 40 bags in 1 palette (1200 kg/palette)

**Storage:**

- Dry mortar bags should be protected from water, frost and adverse air conditions.
- They should be kept dry and cool on wooden pallets.
- The torn and opened products should be closed immediately and consumed first.
- Maximum 6 bags should be stocked on each other.
- Shelf life is maximum 6 months conditional to complying with the abovementioned storage conditions.

**Risk Signs :**

**R23/24/25** : Poisonous when inhaled, swallowed and contacted with skin.

**Security signs:**

**S2:** Keep out of reach of children.

**S3:** Keep cool.

**S9:** Keep the package dry.

**S26:** Rinse with water thoroughly when contacted with eyes and consult a doctor.

**S28:** Rinse with water thoroughly when contacted with skin and consult a doctor.

**S29:** Do not throw in the drain.

**S36/37/39:** Wear suitable protective clothing, protective gloves and glasses / mask during the operation.

---

BOSTIK is only responsible for the product quality and cannot be held responsible for its mis-use except for the recommendations regarding where and/or how the product shall be used. This technical bulletin hereby is valid until it is renewed. BOSTIK's right to amend the products in accordance with technical developments is reserved.



Akçaburgaz Mh. ALKOP Sit. 1575 Sk. C2 Blok No.5-14 Esenyurt 34555 İstanbul  
Tel. (+90 212) 858 01 26 Fax. (+90 212) 858 01 34  
info@bostik.com.tr - www.bostik.com.tr