

# Meister EYA

## Porous Surface Primer

### Product Description:

A transparent blue-coloured primer that enables the coat to be applied afterwards freezing without cracks and increase the capacity to adhere on the surfaces by balancing the absorbency of surfaces.

### Areas of applications:

- Indoors and outdoors
- On walls, ceilings and floors
- On all kinds of stone and stone derivative bricks, pumice concrete, briquette, aerated concrete, concrete plates and exposed concrete

### Features:

- Prevents the plaster from cracks as a result of fast absorption of plaster liquid through the surface
- Prevents air bubbles formation on the surface
- Balances the tensile and drying durations of all kinds of mineral-based plaster
- Enables freezing without cracks by increasing adhesion strength
- Skin-forming happens when dried completely
- Resistant to water, constant humidity and frost after hardened
- Reduces the consumption of the materials to be applied on Meister EYA Primer as it increases the adhesion strength of the surfaces
- Cementitious and anhydrous plaster, mineral plaster and paint can be applied on
- Fireproof

### Technical data:

Colour	Transparent blue
Unit Volume Weight (kg / lt)	1,0 ± 0,2
Wet Volume Weight (kg / lt)	1,7 ± 0,2
Initial Drying Time (hour)	2
Proper Drying Time (hour)	24
Environment temperature for application	Between +5°C and +35°C
Resistance of hardened liquid	Between -25°C and +80°C

Technical data are approximately provided according to a temperature of + 20°C and a relative humidity of 50%. The obtained values increase while exterior environment temperature decreases and it drops while the run temperature increases.

### Preparing the substrate :

- The application surface should be durable, crack-free and able to bear a burden.
- The substances such as dust, residues of cement and paint, and grease and mould oil should be removed from the surface.
- Damaged, worn and weak surfaces should be cleaned from the application surface.
- The application surface should not be more humid than necessary.
- Combing very slippery surfaces such as exposed concrete or glazed concrete are recommended prior to application.

### Application:

- Ready-to-use Meister EYA Primer is applied on the surface with a paint brush or roller brush.
- During the application, do not let lump formation and stir frequently.
- According to the surface specifications, air-conditioning and drying times should be checked carefully.

### Coverage:

Approx. 0.1 - 0,2 kg/m<sup>2</sup> for each layer.

The coverage amounts are theoretical and it is recommended to do coverage-controlled sample application before treatment.

**Packaging:**

In 15 kg plastic buckets

**Storage:**

- They should be protected from frost and adverse air conditions.
- They should be kept in a dry and cool place.
- The opened products should be closed immediately and the drums left open should be disposed.
- Shelf life is maximum 12 months.

**Risk Signs :**

**R23/24/25** : Poisonous when inhaled, swallowed and contacted with skin.

**Security signs:**

**S2:** Keep out of reach of children.

**S3:** Keep cool.

**S9:** Keep the package dry.

**S26:** Rinse with water thoroughly when contacted with eyes and consult a doctor.

**S28:** Rinse with water thoroughly when contacted with skin and consult a doctor.

**S29:** Do not throw in the drain.

**S36/37/39:** Wear suitable protective clothing, protective gloves and glasses / mask during the operation.

---

BOSTIK is only responsible for the product quality and cannot be held responsible for its mis-use except for the recommendations regarding where and/or how the product shall be used. This technical bulletin hereby is valid until it is renewed. BOSTIK's right to amend the products in accordance with technical developments is reserved.



Akçaburgaz Mh. ALKOP Sit. 1575 Sk. C2 Blok No.5-14 Esenyurt 34555 İstanbul  
Tel. (+90 212) 858 01 26 Fax. (+90 212) 858 01 34  
info@bostik.com.tr - www.bostik.com.tr