

NivoTech FilloPrim

Filler Primer

Product Description :

It is a fast-drying, two-component special filling primer for self-levelling screeds that is prepared by reinforcement with environment friendly additives and polymers. It is suitable for absorptive and non-absorptive surfaces with its perfect adhesion and filling quality in addition to its ability to fill the gaps and channels up to 1 mm.

Application areas :

- On all kinds of mineral-based sub-floors
- Indoors and outdoors

Features :

- Reduces the consumption
- Increases the adhesion
- Flexible
- Up to 1 mm filling ability
- Saves time by drying fast
- Suitable for floor heating systems
- Enhances the life of the upper layer
- Ensures more homogenous and constant screed surface

Preparing the substrate :

- Foreign substances that prevent adhesion such as dust, dirt, form oil, scoria, paint and other residues and wastes such as cement, plaster and concrete should be removed from the surface of application.
- Sub-surfaces that are not solid enough to bear their own weight or algae residues should be removed.

Application:

- Two components of Bostik NivoTech FilloPrim are mixed slowly in low cycle until a homogenous mixture is obtained.
- The fresh mixture should be used within 20 minutes.

Coverage:

Approximately 0,200 – 0,600 kg/m²

Attention: It must be stirred prior to use.

Package:

In 17,5 kg plastic drums in sets (12,5 kg powder component + 5,0 kg dispersion)

Storage:

- They should be protected from frost and adverse air conditions.
- They should be kept in a cool and dry place above +5°C and no direct sunlight should be exposed.
- The opened drums should be closed immediately; the drums left open should be disposed.
- Shelf life is maximum 12 months in unopened packages.

Risk Signs :

R23/24/25 : Poisonous when inhaled, swallowed and contacted with skin.

Security signs:

S2: Keep out of reach of children.

S3: Keep cool.

S9: Keep the package dry.

S26: Rinse with water thoroughly when contacted with eyes and consult a doctor.

S28: Rinse with water thoroughly when contacted with skin and consult a doctor.

S29: Do not throw in the drain.

S36/37/39: Wear suitable protective clothing, protective gloves and glasses / mask during the operation.

BOSTIK is only responsible for the product quality and cannot be held responsible for its mis-use except for the recommendations regarding where and/or how the product shall be used. This technical bulletin hereby is valid until it is renewed. BOSTIK's right to amend the products in accordance with technical developments is reserved.



Akçaburgaz Mh. ALKOP Sit. 1575 Sk. C2 Blok No.5-14 Esenyurt 34555 İstanbul
Tel. (+90 212) 858 01 26 Fax. (+90 212) 858 01 34
info@bostik.com.tr - www.bostik.com.tr