

SX Roll

Transparent Surface Protector

Product Description :

Bostik SX Roll is a silane/siloxane-based, ready-to-use, transparent surface protector containing solvent. It features water-repelling quality when applied on surfaces and enriches the durability of the surface making it resistant to weather conditions.

Areas of applications :

- In exteriors only,
- In vertical applications only,
- In natural stones, clinkers, marbles, natural stones and all kinds of mineral-based surfaces.

Features :

- Resistant to alkalis and UV lights.
- Does not form film layer on the surface.
- Does not fade or bubble in the progress of time.
- Extends the life of the building.
- Prevents the pollution in the facades of the buildings.
- Resistant to crack formations on the application surface; no seams are formed.
- Applicable with a brush, easy to apply.

Technical data:

Colour	Transparent
Unit volume weight (kg/ltr)	0,78
Fully dry after (h)	24
Application temperature	Between +5°C and +35°C
Resistance of hardened coat	Between -25°C and +80°C

Technical data are approximately provided according to a temperature of + 20°C and a relative humidity of 50%.

Preparing the substrate :

- The surfaces to be coated should be free of adhesive preventive foreign substances such as dust, dirt, mould oil, paint etc.; residues and wastes like cement, plaster and concrete should also be removed.
- The sub-surfaces that are not strong enough to bear their own weight e.g. cracked plasters, weak surfaces, or residues of moss should be cleaned from the application surface.
- The application surface must definitely be crack-free and strong. The gaps should be filled with Bostik 410 HP.
- Corners should be rounded.
- The surfaces should be dry prior to application.

Application :

- Bostik SX Roll is ready-to-use and should be applied on the surface with a brush or roller.
- It should be applied with a brush and in minimum 2 layers. Second layer should be applied 6 hours later.

After application:

- In the first days, newly applied surfaces should be protected from direct sunlight, severe air stream, high temperatures (over +35°C), adverse air conditions such as rain and frost.

Coverage :

Approx. 0,25 lt / m².

The coverage amounts are theoretical.

Packaging :

5 lt tin.

Storage :

- They should be protected for water, frost and adverse weather conditions.

- Bostik SX Roll contains solvent. Keep fire away in storing and application areas. These areas should be aerated.
- Shelf life is maximum 12 months conditional to complying with the abovementioned storage conditions.

Risk Signs :

R23/24/25 : Poisonous when inhaled, swallowed and contacted with skin.

Security signs:

S2: Keep out of reach of children.

S3: Keep cool.

S9: Keep the package dry.

S26: Rinse with water thoroughly when contacted with eyes and consult a doctor.

S28: Rinse with water thoroughly when contacted with skin and consult a doctor.

S29: Do not throw in the drain.

S36/37/39: Wear suitable protective clothing, protective gloves and glasses / mask during the operation.

BOSTIK is only responsible for the product quality and cannot be held responsible for its mis-use except for the recommendations regarding where and/or how the product shall be used. This technical bulletin hereby is valid until it is renewed. BOSTIK's right to amend the products in accordance with technical developments is reserved.



Akçaburgaz Mh. ALKOP Sit. 1575 Sk. C2 Blok No.5-14 Esenyurt 34555 İstanbul
Tel. (+90 212) 858 01 26 Fax. (+90 212) 858 01 34
info@bostik.com.tr - www.bostik.com.tr